

| | | | |
|---------------------------------|----------------------|----|-------|
| L LENGTH TOLERANCE | > 5/8" to ≤ 1-1/2" | +0 | -0,05 |
| | > 1-1/2" to ≤ 2-3/4" | +0 | -0,06 |
| | > 2-3/4" | +0 | -0,09 |



| | | |
|------------------------------|--------------|-------------|
| S THREAD Length | < 1" | Full Thread |
| | ≥ 1" to ≤ 2" | 2/3 Thread |
| | > 2" | 1/2 Thread |

| SCREW | M PUNCH | | Q Drive Depth | A Head Diam. | E Body Diam. | D Thread Diam. | T Point Length | THREAD Per Inch | TORK Inch / Pound |
|-------|------------|-----|------------------|-----------------|-----------------|-------------------|-------------------|--------------------|----------------------|
| # 8 | # 2 | Min | 0,060 | 0,292 | 0,121 | 0,168 | 0,375 | 10 | 39 |
| | | Max | 0,075 | 0,332 | 0,126 | 0,179 | 0,450 | | |
| # 10 | # 2 | Min | 0,060 | 0.340 | 0.142 | 0.194 | 0.475 | 9 | 56 |
| | | Max | 0,075 | 0.385 | 0.147 | 0.205 | 0.550 | | |

Flat countersunk head with 4 nibs, Square recess, Coarse thread, Type-17, GREEN RUSPERT (pantone 5773C metallic)

Pantone 5773 C

Available in the following Pantone guides:

  **FORMULA GUIDE Solid Coated**
 Page: C 149
[Learn More](#)

PANTONE 5773 C

Date : 15 janvier 2014

Done by : P.B