



|                                 |                      |     |        |
|---------------------------------|----------------------|-----|--------|
| <b>L</b><br>LENGTH<br>TOLERANCE | > 5/8" to ≤ 1-1/2"   | + 0 | - 0.05 |
|                                 | > 1-1/2" to ≤ 2-3/4" | + 0 | - 0.06 |

|                              |      |             |
|------------------------------|------|-------------|
| <b>S</b><br>THREAD<br>LENGTH | < 1" | Full Thread |
|                              | ≥ 1" | 2/3 Thread  |

| SCREW | M<br>PUNCH |     | Q<br>DRIVE DEPTH | A<br>HEAD DIAM. | E<br>BODY DIAM. | D<br>THREAD DIAM. | THREAD<br>PER INCH | TORK<br>INCH/ POUND |
|-------|------------|-----|------------------|-----------------|-----------------|-------------------|--------------------|---------------------|
| # 6   | # 2        | Min | 0.048            | 0.244           | 0.103           | 0.142             | 12                 | 24                  |
|       |            | Max | 0.063            | 0.279           | 0.108           | 0.153             |                    |                     |

Flat countersunk head with 4 nibs, Square recessed, Coarse thread, Plain

Date: 18 novembre 2009

Fait par: D.G.