



unit: INCH

<b>L</b> LENGTH TOLERANCE	>5/8" to ≤1-1/2"	+0	-0,05
	>1-1/2" to ≤2-3/4"	+0	-0,06
	>2-3/4"	+0	-0,09

<b>S</b> THREAD	< 1"	Full Thread
	≥ 1"	2/3 Thread

SCREW	M PUNCH		Q DRIVE DEPTH	H HEAD HEIGHT	U WASH. HEIGHT	W WASHER DIAM.	A HEAD DIAM.	E BODY DIAM.	D THREAD DIAM.	THREAD PER INCH	TORK INCH/ POUND
# 6	# 1	Min	0,050	0,084	REF 0,040	0,301	REF 0,218	0,103	0,142	12	24
		Max	0,065	0,096		0,321		0,108			
# 8	# 2	Min	0,060	0,101	REF 0,040	0,358	REF 0,259	0,121	0,168	10	39
		Max	0,075	0,113		0,380		0,126			
# 10	# 2	Min	0,060	0,118	REF 0,050	0,416	REF 0,300	0,142	,194	9	54
		Max	0,075	0,130		0,439		0,147			

Pan Washer head, Square recessed, Coarse thread, Zinc

Date: 18 mars 2013

Fait par: D.G.